



TOOL FEATURES

1. Steel, adjustable hammer exhaust.
 2. Rubber protection pad protects work surface.
 3. Depth adjust device front protection plate.
 4. Long narrow nose provides improved line of sight.
 5. Magnesium ergonomic frame over-molded handle grip.
 6. Magnesium casted one-piece connector with industry leading durability.
 7. Rear- jam clearance investment-casted protector minimizes downtime and maximizes tool durability.
- Loading capacity : SN50LM series **340 staples**
SN40LM series **310 staples**
SN503MAG series **480 staples**

AVAILABLE VARIATIONS

Machine-Mounted Version	Equipped with RCVA1 or RVCA2 remote control trigger valve
Long Magazine Kit	Furnished with magazine assembly only, model dependent
Hand-Held Version	Equipped with standard sequential or contact fire trigger
Full-Auto Version	Equipped with full-automatic cap assembly, shoots up to 20 staples/sec

FASTENER SPECS

SN50S5LM	16 & 17 GA. Bostitch BCS5 / SENC0 N / BeA 155
SN50S4LM	16 GA. Bostitch BCS4 / Atr0 16 NC
SN402PLM	16 GA. Senco P / Prebena WS
SN402S2LM	16 GA. Bostitch BCS2 / Prebena WC
SN50S53MAG	16 & 17 GA. Bostitch BCS5 / SENC0 N / BeA 155

TOOL SPECS

Weight	LM : 2.7 kgs (5.9 lbs) 3MAG : 3.1 kgs (6.8 lbs)
Height	SN40 : 251mm (9.9") SN50 : 272mm (10.7")
Width	94mm (3.7")
Length	LM : 570mm (22.4") 3MAG : 777mm (30.6")
Operating Pressure	5~8 bar (70~120 psi)
Driving Power	SN40 : 397 In-lbs @100 psi SN50 : 369 In-lbs @100 psi
Applications	Machine-mounted Automatic Operation

